

PRODUCT-DETAILS

ACS310-03E-05A2-2

ACS310-03E-05A2-2 Pn 0,75, I2n 5,2A IP20



General Information

| | |
|-------------------------|--|
| Global Commercial Alias | ACS310-03E-05A2-2 |
| Product ID | 3AUA0000039192 |
| ABB Type Designation | ACS310-03E-05A2-2 |
| EAN | 6410038785628 |
| Catalog Description | ACS310-03E-05A2-2 Pn 0,75, I2n 5,2A IP20 |

Ordering

| | |
|-------------------------|--|
| Country of Origin | China (CN) Finland (FI) |
| Customs Tariff Number | 85044084 |
| EAN | 6410038785628 |
| Invoice Description | ACS310-03E-05A2-2 Pn 0,75, I2n 5,2A IP20 |
| Made To Order | No |
| Minimum Order Quantity | 1 piece |
| Order Multiple | 1 piece |
| Quote Only | No |
| Selling Unit of Measure | piece |
| Stocked At (Warehouses) | Central Stock Europe FIPSEEXPU US Drive Services |

FIPSEEXPU014
 SGRDC002EXPU
 CNIAB001EXPU
 SGIND002EXPU
 JPABB001EXPU
 AUABB024EXPU

Dimensions

| | |
|--------------------|--------|
| Product Net Height | 344 mm |
| Product Net Length | 217 mm |
| Product Net Weight | 1.8 kg |
| Product Net Width | 132 mm |

Technical

| | |
|----------------------------------|---------------|
| Enclosure Class | IP20 |
| Frequency (f) | 50/60 Hz |
| Input Voltage (U_{in}) | 200 ... 240 V |
| Mounting Type | Wall-mounted |
| Number of Phases | 3 |
| Output Current, Normal Use | 5.2 A |
| Output Power, Light-Overload Use | 0.75 kW |
| Output Power, Normal Use | 0.75 kW |

Additional Information

| | |
|-------------------|---------------------|
| Product Main Type | ACS310 |
| Product Name | Frequency converter |

Classifications

| | |
|----------------|--------|
| Product Series | ACS310 |
|----------------|--------|

Categories

Drives → Low voltage AC drives → General purpose drives → ACS310 - Drive module for pumps and fans

