

CP Rigid/Intermediate Grade Conduit Fittings

- Insulated Throat Grounding Bushings
- Threaded and Threadless
- Copper or Aluminum Ground Lug
- 105°C Rated

INSULATED THROAT GROUNDING BUSHINGS

IRON-105°C Rated Plastic Throat Liner

Copper Lug – For Copper Grounding Conductors – Threaded

UL File No. E-6225

Cat. #	Trade Size	Lug Size	Unit Qty.	Std. Pkg.	Weight Lbs. Per 100
GLL-1C	1/2"	#4 – #14	50	500	8
GLL-2C	3/4"	#4 – #14	50	250	12
GLL-3C	1"	#4 – #14	50	250	14
GLL-4C	1 1/4"	#4 – #14	25	125	19
GLL-4-10C	1 1/4"	#1/0 – #8	25	125	30
GLL-5C	1 1/2"	#4 – #14	10	100	21
GLL-5-10C	1 1/2"	#1/0 – #8	10	100	32
GLL-6C	2"	#4 – #14	10	50	29
GLL-6-10C	2"	#1/0 – #8	10	50	40
GLL-7C	2 1/2"	#1/0 – #8	10	50	65
GLL-7-30C	2 1/2"	#3/0 – #6	10	50	88
GLL-7-250C	2 1/2"	250MCM – #6	10	50	97
GLL-8C	3"	#1/0 – #8	5	25	77
GLL-8-30C	3"	#3/0 – #6	5	25	100
GLL-8-250C	3"	250MCM – #6	5	25	109
GLL-9C	3 1/2"	#3/0 – #6	1	1	125
GLL-9-250C	3 1/2"	250MCM – #6	1	1	134
GLL-10C	4"	#3/0 – #6	1	1	145
GLL-10-250C	4"	250MCM – #6	1	1	154
GLL-11C	5"	#3/0 – #6	1	1	165
GLL-11-250C	5"	250MCM – #6	1	1	174
GLL-12C	6"	#3/0 – #6	1	1	195
GLL-12-250C	6"	250MCM – #6	1	1	204

Aluminum Lug – For Copper Or Aluminum Grounding Conductors – Threaded 105°C Rated Plastic Throat Liner

UL File No. E-6225

Cat. #	Trade Size	Lug Size	Unit Qty.	Std. Pkg.	Weight Lbs. Per 100
GLL-1	1/2"	#4 – #14	50	500	5
GLL-2	3/4"	#4 – #14	50	250	9
GLL-3	1"	#4 – #14	50	250	12
GLL-4	1 1/4"	#4 – #14	25	125	19
GLL-4-10	1 1/4"	#1/0 – #8	25	125	23
GLL-5	1 1/2"	#4 – #14	10	100	24
GLL-5-10	1 1/2"	#1/0 – #8	10	100	28
GLL-6	2"	#4 – #14	10	50	26
GLL-6-10	2"	#1/0 – #8	10	50	32
GLL-7	2 1/2"	#1/0 – #8	10	50	53
GLL-7-30	2 1/2"	#3/0 – #6	10	50	60
GLL-7-250	2 1/2"	250MCM – #6	10	50	67
GLL-8	3"	#1/0 – #8	5	25	70
GLL-8-30	3"	#3/0 – #6	5	25	72
GLL-8-250	3"	250MCM – #6	5	25	76
GLL-9	3 1/2"	#3/0 – #6	1	1	100
GLL-9-250	3 1/2"	250MCM – #6	1	1	100
GLL-10	4"	#3/0 – #6	1	1	110
GLL-10-250	4"	250MCM – #6	1	1	120
GLL-11	5"	#3/0 – #6	1	1	140
GLL-11-250	5"	250MCM – #6	1	1	143
GLL-12	6"	#3/0 – #6	1	1	160
GLL-12-250	6"	250MCM – #6	1	1	163

Copper Lug – For Copper Grounding Conductors – Threadless – Set Screw Type 105°C Rated Plastic Throat Liner

UL File No. E-6225

Cat. #	Trade Size	Lug Size	Unit Qty.	Std. Pkg.	Weight Lbs. Per 100
GLS-1C	1/2"	#4 – #14	50	500	8
GLS-2C	3/4"	#4 – #14	50	250	12
GLS-3C	1"	#4 – #14	50	250	14
GLS-4C	1 1/4"	#4 – #14	25	125	19
GLS-4-10C	1 1/4"	#1/0 – #8	25	125	30
GLS-5C	1 1/2"	#4 – #14	10	100	21
GLS-5-10C	1 1/2"	#1/0 – #8	10	100	32
GLS-6C	2"	#4 – #14	10	50	29
GLS-6-10C	2"	#1/0 – #8	10	50	40
GLS-7C	2 1/2"	#1/0 – #8	10	50	65
GLS-7-30C	2 1/2"	#3/0 – #6	10	50	88
GLS-7-250C	2 1/2"	250MCM – #6	10	50	97
GLS-8C	3"	#1/0 – #8	5	25	77
GLS-8-30C	3"	#3/0 – #6	5	25	100
GLS-8-250C	3"	250MCM – #6	5	25	109
GLS-9C	3 1/2"	#3/0 – #6	1	1	125
GLS-9-250C	3 1/2"	250MCM – #6	1	1	134
GLS-10C	4"	#3/0 – #6	1	1	145
GLS-10-250C	4"	250MCM – #6	1	1	154
GLS-11C	5"	#3/0 – #6	1	1	165
GLS-11-250C	5"	250MCM – #6	1	1	174
GLS-12C	6"	#3/0 – #6	1	1	195
GLS-12-250C	6"	250MCM – #6	1	1	204

Aluminum Lug – For Copper Or Aluminum Grounding Conductors – Threadless – Set Screw Type 105°C Rated Plastic Throat Liner

UL File No. E-6225

Cat. #	Trade Size	Lug Size	Unit Qty.	Std. Pkg.	Weight Lbs. Per 100
GLS-1	1/2"	#4 – #14	50	500	5
GLS-2	3/4"	#4 – #14	50	250	9
GLS-3	1"	#4 – #14	50	250	12
GLS-4	1 1/4"	#4 – #14	25	125	19
GLS-4-10	1 1/4"	#1/0 – #8	25	125	23
GLS-5	1 1/2"	#4 – #14	10	100	24
GLS-5-10	1 1/2"	#1/0 – #8	10	100	28
GLS-6	2"	#4 – #14	10	50	26
GLS-6-10	2"	#1/0 – #8	10	50	32
GLS-7	2 1/2"	#1/0 – #8	10	50	53
GLS-7-30	2 1/2"	#3/0 – #6	10	50	60
GLS-7-250	2 1/2"	250MCM – #6	10	50	67
GLS-8	3"	#1/0 – #8	5	25	70
GLS-8-30	3"	#3/0 – #6	5	25	72
GLS-8-250	3"	250MCM – #6	5	25	76
GLS-9	3 1/2"	#3/0 – #6	1	1	100
GLS-9-250	3 1/2"	250MCM – #6	1	1	100
GLS-10	4"	#3/0 – #6	1	1	110
GLS-10-250	4"	250MCM – #6	1	1	120
GLS-11	5"	#3/0 – #6	1	1	140
GLS-11-250	5"	250MCM – #6	1	1	143
GLS-12	6"	#3/0 – #6	1	1	160
GLS-12-250	6"	250MCM – #6	1	1	163