

483530



RATED CURRENT		25 A	32 A	32 A	30 A
RATED VOLTAGE		400 V	690 V	690 V	600 V
RATED POWER DISSIPATION		3 W	3 W	3 W	3 W
UTILIZATION CATEGORY		AC-20	AC-20	AC-22B 500V AC-21B 690 V	–
PROTECTION DEGREE		IP-20	IP-20	IP-20	IP-20
OPERATING TEMPERATURE		-20 ... 70 °C	-20 ... 70 °C	-20 ... 70 °C	-20 ... 70 °C
STORAGE TEMPERATURE		-40 ... 80 °C	-40 ... 80 °C	-40 ... 80 °C	-40 ... 80 °C
DERATING TEMPERATURE	20 °C	1	1	1	1
	30 °C	0,95	0,95	0,95	0,95
	40 °C	0,9	0,9	0,9	0,9
	50 °C	0,8	0,8	0,8	0,8
DERATING N° OF POLES	1 ... 4	1	1	1	1
	5 ... 6	0,8	0,8	0,8	0,8
	7 ... 9	0,7	0,7	0,7	0,7
	≥ 10	0,6	0,6	0,6	0,6
FIXING	RAIL DIN / EN	•	•	•	•
	SCREW	–	–	–	–
CONNECTING WIRE		0,75...6 mm ² STRAINED	0,75...6 mm ² STRAINED	0,75 ... 16 mm ² STRAINED 0,75 ... 25 mm ² SOLID	0,75...16 mm ² STRAINED
		0,75...10 mm ² SOLID	0,75...10 mm ² SOLID	0,75...10 mm ² STRAINED (1P+N 1M) 0,75...16 mm ² SOLID (1P+N 1M)	0,75...16 mm ² SOLID
WITH LIGHTNING INDICATOR		–	–	120...690V AC 12...24V DC	120...690V AC 12...24V DC
MAX. TIGHTENING TORQUE		2 Nm	2 Nm	2,5 Nm 2 Nm (1P+N 1M)	2,5 Nm
WITH MICROSWITCH 5A-250V	FUSING	–	–	–	•
	PREBREAKING PRESENCE FUSING	–	–	–	•
		•	•	•	•
MULTIPOLAR UNION WITH ACCESSORIES		•	•	•	•
LABEL HOLDER		–	–	–	•
LOCKING ACCESSORIES		–	–	–	•

STANDARDS

