

Clavijas y tomas de corriente industriales >50V

■ BASES EMPOTRABLES - IP44

Serie EUREKA

Polos	Hz.	Volts	Color	INCLINADA BRIDA DE FIJACIÓN NORMAL		RECTA BRIDA DE FIJACIÓN REDUCIDA 75x75	
				16A	32A	16A	32A
2P+T	50/60	100-130	■	70x87 10/60 ^(*)	84x106 10/40	75x75 10/100	75x75 10/50
	50/60	200-250	■	412.1660	412.3260	422.1660R ^(*)	422.3260
	50/60	380-415	■	412.1663	412.3263	422.1663(A)	422.3263
	50/60	480-500	■	412.1668	412.3268	422.1668	422.3268
3P+N+T	50/60	480-500	■	412.1668	412.3268	422.1668R ^(*)	422.3268
	50/60	trasf.	■	422.16636	422.32636	422.16636	422.32636
	>300-500	>50	■	422.16633	422.32633	422.16633	422.32633
	c.c.	>50-250	■	422.16632	422.32632	422.16632	422.32632
4	c.c.	>50-250	■	422.16634	422.32634	422.16634	422.32634
	50/60	100-130	■	422.16638	422.32638	422.16638	422.32638
	50/60	200-250	■	422.1661	422.3261	422.1661	422.3261
	50/60	380-415	■	412.1664	412.3264	422.1664	422.3264
3P+T	50/60	440-460	■	412.1666	412.3266	422.1666	422.3266
	60	440-460	■	422.16665	422.32665	422.16665	422.32665
	50/60	480-500	■	422.16666	422.32666	422.16666	422.32666
	50/60	600-690	■	422.16667	422.32667	422.16667	422.32667
3P+N+T	50	380-440	■	422.16664	422.32664	422.16664	422.32664
	60	380-440	■	422.16664	422.32664	422.16664	422.32664
	100-300	>50	■	422.16661	422.32661	422.16661	422.32661
	>300-500	>50	■	422.16662	422.32662	422.16662	422.32662
3P+N+T	50/60	100-130	■	412.1662	412.3262	422.1662	422.3262
	50/60	208-250	■	412.1665	412.3265	422.1665	422.3265
	50/60	346-415	■	412.1667	412.3267	422.1667	422.3267
	50/60	480-500	■	422.16676	422.32676	422.16676	422.32676
3P+N+T	50/60	600-690	■	422.16677	422.32677	422.16677	422.32677
	60	440-460	■	422.16675	422.32675	422.16675	422.32675
	50	380-440	■	422.16674	422.32674	422.16674	422.32674
	>300-500	>50	■	422.16672	422.32672	422.16672	422.32672

(*) Flange 62x62 mm

Tensión nominal >50V

-Aprobaciones: de pág. 561



Bornes de tornillo



Bornes de resorte

Más información de pág. 36



(A) Brida de color negro

Versiones también disponible con brida negra artículos 422.1663K y 422.1663PK.

Serie EUREKA

452.



413.

(*)



Serie OPTIMA

Polos	Hz.	Volts	Color	CON SALIDA A 90°		INCLINADA BRIDA DE FIJACIÓN NORMAL		SAFE-IN INCLINADA BRIDA DE FIJACIÓN NORMAL		FAST WIRING INCLINADA BRIDA DE FIJACIÓN NORMAL	
				16A	32A	16A	32A	16A	32A	16A	32A
2P+T	50/60	100-130	■	70x87 10/60 ^(*)	84x106 10/40	70x87 10/100	84x106 10/50	70x87 10/100	84x106 10/50	70x87 10/100	84x106 10/50
	50/60	200-250	■	452.3260	452.3263	413.1660	413.3260	413.1660H	413.3260F	413.1660F	413.3260F
	50/60	380-415	■	452.3268	452.3268	413.1663	413.3263	413.1663H	413.3263F	413.1663F	413.3263F
	50/60	480-500	■	452.32636	452.32636	413.1668	413.3268	413.1668H	413.3268F	413.1668F	413.3268F
3P+N+T	50/60	480-500	■	452.32636	452.32636	413.16636	413.32636	413.16636	413.32636	413.16636	413.32636
	>300-500	>50	■	452.32633	452.32633	413.16633	413.32633	413.16633	413.32633	413.16633	413.32633
	c.c.	>50-250	■	452.32632	452.32632	413.16632	413.32632	413.16632	413.32632	413.16632	413.32632
	c.c.	>50-250	■	452.32634	452.32634	413.16634	413.32634	413.16634	413.32634	413.16634	413.32634
4	50/60	100-130	■	452.32638	452.32638	413.16638	413.32638	413.16638	413.32638	413.16638	413.32638
	50/60	200-250	■	452.3261	452.3261	413.1661	413.3261	413.1661	413.3261	413.1661	413.3261
	50/60	380-415	■	452.3264	452.3264	413.1664	413.3264	413.1664H	413.3264F	413.1664F	413.3264F
	60	440-460	■	452.3266	452.3266	413.1666	413.3266	413.1666H	413.3266F	413.1666F	413.3266F
3P+T	50/60	480-500	■	452.32665	452.32665	413.16665	413.32665	413.16665	413.32665	413.16665	413.32665
	50/60	600-690	■	452.32666	452.32666	413.16666	413.32666	413.16666	413.32666	413.16666	413.32666
	50	380-440	■	452.32667	452.32667	413.16667	413.32667	413.16667	413.32667	413.16667	413.32667
	60	380-440	■	452.32664	452.32664	413.16664	413.32664	413.16664	413.32664	413.16664	413.32664
3P+N+T	100-300	>50	■	452.32661	452.32661	413.16661	413.32661	413.16661	413.32661	413.16661	413.32661
	>300-500	>50	■	452.32662	452.32662	413.16662	413.32662	413.16662	413.32662	413.16662	413.32662
	50/60	100-130	■	452.3262	452.3262	413.1662	413.3262	413.1662	413.3262	413.1662	413.3262
	50/60	208-250	■	452.3265	452.3265	413.1665	413.3265	413.1665	413.3265	413.1665	413.3265
3P+N+T	50/60	346-415	■	452.3267	452.3267	413.1667	413.3267	413.1667H	413.3267F	413.1667F	413.3267F
	50/60	480-500	■	452.32676	452.32676	413.16676	413.32676	413.16676	413.32676	413.16676	413.32676
	50/60	600-690	■	452.32677	452.32677	413.16677	413.32677	413.16677	413.32677	413.16677	413.32677
	60	440-460	■	452.32675	452.32675	413.16675	413.32675	413.16675	413.32675	413.16675	413.32675
3P+N+T	50	380-440	■	452.32674	452.32674	413.16674	413.32674	413.16674	413.32674	413.16674	413.32674
	60	380-440	■	452.32674	452.32674	413.16674	413.32674	413.16674	413.32674	413.16674	413.32674
	>300-500	>50	■	452.32672	452.32672	413.16672	413.32672	413.16672	413.32672	413.16672	413.32672

(*) 2P+E= 10/100



(B) De color negro

Versiones también disponible en negro; solo agregar "K" al final de cada referencia. Ejemplo: 413.1663.K



Ideales para cuadro Serie DOMINO (pág. 137) y Serie BLOCK (pág. 144)



Accesorios

Cajas vacías para realizar versiones murales pág. 60