

**Article**

**603.3505-062**  
 3-WAY ADAPTOR IP66

**Picture****Master data**

|                                 |               |
|---------------------------------|---------------|
| Minimum order                   | 1 NR          |
| Net Weight                      | 0.865 KG      |
| EAN code                        | 8001636041872 |
| Harmonized System Code (HSCode) | 85366990      |

**TechData**

|                          |                                  |
|--------------------------|----------------------------------|
| Commercial series        | ADAPTO Series                    |
| Synthetical description  | MULTI-WAY ADAPTOR                |
| Protection degree IP     | IP66                             |
| Inlet supply unit        | Terminal block 16mm <sup>2</sup> |
| Rated current            | 16A                              |
| Poles                    | 2P+E                             |
| Rated voltage            | 230V                             |
| No. of sockets 2P +E 16A | 3                                |

**Approvals and Certifications**

UE  
 Declaration of conformity



EAC  
 Eurasian Conformity

**Standards and Laws**

IEC 60309-1 (1999)  
 [International Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 1: General requirements



IEC 60309-2 (1999)  
 [International Standard] Plugs, socket-outlets and couplers for industrial purposes. Part: 2: Dimensional interchangeability requirements for pin and contact-tube accessories

**Packaging**

|              |               |
|--------------|---------------|
| Description  | Carton        |
| Quantity     | 10            |
| EAN code     | 8001636946801 |
| Gross weight | 10.95 KG      |
| Volume       | 70840 CCM     |

**Annexed**

Technical drawing [DWG]



Technical drawing [PDF]

|              |                  |
|--------------|------------------|
| Dimensions   | 280x440x575 (MM) |
| Description  | Box              |
| Quantity     | 1                |
| EAN code     | 8001636933535    |
| Gross weight | 1.095 KG         |
| Volume       | 5890.104 CCM     |
| Dimensions   | 198x268x111 (MM) |



Technical drawing [STP]

**Note:**

> Zinc-plated steel carrying handle.



> Equipped with PG21 cable gland, cable clamp and terminal block.

**Technical Details**

|                                  |                    |
|----------------------------------|--------------------|
| 2P+E                             | Poles              |
| ADAPTO Series                    | Commercial series  |
| 16A                              | Rated current      |
| Terminal block 16mm <sup>2</sup> | Inlet supply unit  |
| AC                               | Type of current    |
| IP66                             | Protection degree  |
| IEC 60309-1 (1999)               | Reference standard |
| IEC 60309-2 (1999)               | Reference standard |
| CEILING MOUNTING                 | Mounting version   |
| 230V                             | Rated voltage      |
| Without cable and plug           | Version            |