

CABLE TIE ORDERING SPECIFICATION

GT – 100 M C B V0
1 2 3 4 5 6

- 1** Type
- 2** Length
- 3** Width ————— M=Miniature, I=Intermediate, ST=Standard, HD=Heavy Duty, EHD=Extra Heavy Duty
- 4** Package ————— C=100pcs/bag(Others are 1000pcs/bag)
- 5** Color ————— Non=Natural, B=Black, BR=Brown, RD=Red, OR=Orange, YL=Yellow, GN=Green, BL=Blue, PP=Purple, GY=Gray, WT=White
- 6** Material ————— UV=Ultra Violet weather resistant tie for outdoor application, Heat=Heat Resistant, V0=Flame retardant




MATERIAL DESCRIPTIONS



Material	Operation Temperature		UL Flame Rating	UV Resistance
	Max.	Min.		
Polyamide 6.6	85°C 185°F	-40°C -40°F	94V-2	-
Polyamide 6.6 Heat Resistant	120°C 248°F	-40°C -40°F	94V-2	-
Polyamide 6.6 UV Resistant	85°C 185°F	-40°C -40°F	94V-2	☒
Polyamide 6.6 Flame Retardant	85°C 185°F	-40°C -40°F	UL94 V0	☒
Polyamide 11/12	80°C 176°F	-40°C -40°F	94V-HB	☒
Tefzel®	150°C 302°F	-46°C -50.8°F	94V-0	☒
Stainless Steel Type: #304, 316	500°C 932°F	-80°C -112°F	-	☒
PE	80°C 176°F	-40°C -40°F	94V-HB	-


*Tefzel® is registered trademark of DuPont de Nemours.

CABLE TIES

- Available in a wide range of materials.
- Internal serrations allowing for a positive hold onto cable and pipe bundles.
- The design of the head guarantees a high tensile strength while allowing a very low insertion force.
- Fire-resistant, Heat-resistant, UV resistant are available.
- Material: UL approved Polyamide 6.6, 94V-2
- Color: All colors are available



Part No.	100pcs/bag	Length mm (inch)	Width mm (inch)	Max.Bundle Dia. mm (inch)	Min. Loop Tensile Strength kg (lbs)	Recommended Crimping Tools
GT-90MC	90 (3.54)	2.4 (0.09)	16 (0.63)	8.0 (17.68)		
GT-100MC	100 (3.94)	2.5 (0.10)	22 (0.87)	8.1 (18)		
GT-120MC	120 (4.72)	2.5 (0.10)	30 (1.18)	8.1 (18)		
GT-140MC	140 (5.51)	2.5 (0.10)	33 (1.30)	8.1 (18)		
GT-150MC	150 (5.91)	2.5 (0.10)	35 (1.38)	8.1 (18)		
GT-160MC	160 (6.30)	2.5 (0.10)	40 (1.57)	8.1 (18)		
GT-200MC	200 (7.87)	2.5 (0.10)	53 (2.09)	8.1 (18)		
GT-250MC	250 (9.84)	2.8 (0.11)	65 (2.56)	14 (31)		
GT-300MC	300 (11.81)	2.8 (0.11)	76 (2.99)	14 (31)		
GT-140ISC	140 (5.51)	3.4 (0.13)	33(1.30)	13.6 (30)	 GIT-702P  GIT-702M	
GT-120IC	120 (4.72)	3.6 (0.14)	30 (1.18)	18.2 (40)		
GT-140 IC	140 (5.51)	3.6 (0.14)	33 (1.30)	18.2 (40)		
GT-150IC	150 (5.91)	3.6 (0.14)	35 (1.38)	18.2 (40)		
GT-180IC	180 (7.09)	3.6 (0.14)	44 (1.73)	18.2 (40)		
GT-200IC	200 (7.87)	3.6 (0.14)	53 (2.09)	18.2 (40)		
GT-215IC	215 (8.46)	3.6 (0.14)	56 (2.20)	18.2 (40)		
GT-250IC	250 (9.84)	3.6 (0.14)	65 (2.56)	18.2 (40)		

Part No.		Length mm (inch)	Width mm (inch)	Max.Bundle Dia. mm (inch)	Min. Loop Tensile Strength kg (lbs)	Recommended Crimping Tools
	100pcs/bag					
	GT-280IC	280 (11.02)	3.6 (0.14)	69 (2.72)	18.2 (40)	 GIT-702P
	GT-300IC	300 (11.81)	3.6 (0.14)	76 (2.99)	18.2 (40)	
	GT-360IC	360 (14.17)	3.6 (0.14)	98 (3.86)	18.2 (40)	
	GT-370IC	370 (14.57)	3.6 (0.14)	102 (4.02)	18.2 (40)	
	GT-120STC	120 (4.72)	4.8 (0.19)	24 (0.94)	22.2 (50)	
	GT-150STC	150 (5.91)	4.8 (0.19)	35 (1.38)	22.2 (50)	
	GT-160STC	160 (6.30)	4.8 (0.19)	38 (1.50)	22.2 (50)	
	GT-178STC	178 (7.01)	4.8 (0.19)	40 (1.57)	22.2 (50)	
	GT-190STC	188 (7.40)	4.8 (0.19)	46 (1.81)	22.2 (50)	
	GT-200STC	200 (7.87)	4.8 (0.19)	50 (1.97)	22.2 (50)	
	GT-216STC	215 (8.46)	4.8 (0.19)	53 (2.09)	22.2 (50)	
	GT-250STC	250 (9.84)	4.8 (0.19)	60 (2.36)	22.2 (50)	
	GT-266STC	265 (10.43)	4.8 (0.19)	65 (2.56)	22.2 (50)	
	GT-280STC	280 (11.02)	4.8 (0.19)	70 (2.76)	22.2 (50)	
	GT-300STC	300 (11.81)	4.8 (0.19)	76 (2.99)	22.2 (50)	
	GT-360ST	360 (14.17)	4.8 (0.19)	98 (3.86)	22.2 (50)	
	GT-370ST	370 (14.57)	4.8 (0.19)	102 (4.02)	22.2 (50)	
	GT-390ST	390 (15.35)	4.8 (0.19)	105 (4.13)	22.2 (50)	
	GT-430ST	430 (16.93)	4.8 (0.19)	110 (4.33)	22.2 (50)	
	GT-450ST	450 (17.72)	4.8 (0.19)	116 (4.57)	22.2 (50)	
	GT-530ST	530 (20.87)	4.8 (0.19)	140 (5.51)	22.2 (50)	
	GT-550ST	550 (21.65)	4.8 (0.19)	145 (5.71)	22.2 (50)	
	GT-635ST	635 (25.00)	4.8 (0.19)	190 (7.48)	22.2 (50)	
	GT-685ST	685 (26.97)	4.8 (0.19)	205 (8.07)	22.2 (50)	
	GT-730ST	735 (28.94)	4.8 (0.19)	224 (8.82)	40 (88)	
	GT-830ST	830 (32.68)	4.8 (0.19)	254 (10.00)	40 (88)	
	GT-920ST	925 (36.42)	4.8 (0.19)	263 (10.35)	40 (88)	
	GT-150HD	150 (5.91)	7.6 (0.30)	33 (1.30)	54.4 (120)	
	GT-200HD	200 (7.87)	7.6 (0.30)	50 (1.97)	54.4 (120)	
	GT-240HD	240 (9.45)	7.6 (0.30)	63 (2.48)	54.4 (120)	
	GT-250HD	250 (9.84)	7.6 (0.30)	65 (2.56)	54.4 (120)	
	GT-280HD	280 (11.02)	7.6 (0.30)	71 (2.80)	54.4 (120)	
	GT-300HD	300 (11.81)	7.6 (0.30)	76 (2.99)	54.4 (120)	
	GT-370HD	368 (14.49)	7.6 (0.30)	102 (4.02)	54.4 (120)	
	GT-430HD-S	430 (16.93)	7.6 (0.30)	125 (4.92)	54.4 (120)	
	GT-450HD-S	450 (17.72)	7.6 (0.30)	132 (5.20)	54.4 (120)	
	GT-540HD-S	533 (20.98)	7.6 (0.30)	140 (5.51)	54.4 (120)	
	GT-750HD-S	750 (29.53)	7.6 (0.30)	218 (8.58)	54.4 (120)	




GIT-702P



GIT-702M



GIT-704

Part No.		Length mm (inch)	Width mm (inch)	Max.Bundle Dia. mm (inch)	Min. Loop Tensile Strength kg (lbs)	Recommended Crimping Tools
	100pcs/bag					
	GT-290HD	290 (11.42)	9.0 (0.35)	80.4 (3.16)	79.4 (175)	 GIT-704
	GT-380HD	380 (14.96)	9.0 (0.35)	92.2 (3.63)	79.4 (175)	
	GT-430HD	430 (16.93)	9.0 (0.35)	110 (4.33)	79.4 (175)	
	GT-450HD	450 (17.72)	9.0 (0.35)	120 (4.72)	79.4 (175)	
	GT-530HD	526 (20.71)	9.0 (0.35)	140 (5.51)	79.4 (175)	
	GT-630HD	610 (24.02)	9.0 (0.35)	187 (7.00)	79.4 (175)	
	GT-710HD	710 (27.95)	9.0 (0.35)	190 (7.48)	79.4 (175)	
	GT-780HD	776 (30.55)	9.0 (0.35)	228 (8.98)	79.4 (175)	
	GT-830HD	815 (32.09)	9.0 (0.35)	239 (9.41)	79.4 (175)	
	GT-920HD	912 (35.91)	9.0 (0.35)	263 (10.35)	79.4 (175)	
	GT-1020HD	1020 (40.16)	9.0 (0.35)	295 (11.61)	79.4 (175)	
	GT-1070HD	1070 (42.13)	9.0 (0.35)	320 (12.60)	79.4 (175)	
	GT-1220HD	1220 (48.03)	9.0 (0.35)	365 (14.37)	79.4 (175)	
	GT-1370HD	1375 (54.13)	9.0 (0.35)	412 (16.22)	79.4 (175)	
	GT-1530HD	1530 (60.24)	9.0 (0.35)	460 (18.11)	79.4 (175)	