

SNAP-IN CONVENIENCE OUTLETS

2-Pole • 3-Wire Grounding



CONVENIENCE OUTLETS
AND RECEPTACLES




1374-500

Snap-In Convenience Outlets 1374 Series

Leviton 3-wire grounding outlets are available with serrated or pointed clip styles and wire leads or quick-connect tabs.


- 15A-125V • CSA Certified LR-2781 • NEMA 5-15R



Devices with solder lugs are UL Recognized  E-13399
Cat. No. 1374-500 and devices with terminal screws are
UL Listed E-13399 and NOM Certified 057

Cat. No.	Standard Clip Style	Ground Connection	Hot & Neutral Termination
1374-500	.025" (0.64)* Pointed	6" Wire Lead	Quick Connect Tabs
1374-625	Serrated	Solder Lug	6" Wire Leads
1374-650	.025"(0.64)* Pointed	Solder Lug	6" Wire Leads
1374-675	.025"(0.64)* Pointed	Solder Lug	Quick Connect Tabs
1374-725	Serrated	Screw Terminal	6" Wire Leads
1374-750	.025"(0.64)* Pointed	Screw Terminal	6" Wire Leads
1374-775	.025"(0.64)* Pointed	Screw Terminal	Quick Connect Tabs

*Can also be specified with a .020"(0.51) Pointed Clip.



Important: please specify panel thickness and clip style:

For .031"-.080" (0.79-2.03)—
steel pointed clip or serrated clip

For .080"-.125" (2.03-3.18)—
steel serrated clip only