



# Electronic semi-parallel ignitor for HID lamp circuits

## SN 57

HID ignitors for semi-parallel systems


### Product data

General Information	
Application Code	57
Operating and Electrical	
Input Voltage	220 to 240 V
Input Frequency	50 to 60 Hz
Igniton Type	Semi-Parallel
Ignition Voltage (Max)	2.5 kV
Ignition Voltage (Min)	1.8 kV
Response Voltage	195 V
Mains Voltage Performance (AC)	-8%~+6%
Mains Voltage Safety (AC)	-10%~+10%
Power Losses (Nom)	0.2 W
Wiring	
Ballast Contact Wire Cross Section	0.50-2.50 mm <sup>2</sup>
Connector Type	Screw
Temperature	
T-Ambient (Max)	75 °C

T-Ambient (Min)	-20 °C
T-Case Maximum (Max)	80 °C
Mechanical and Housing	
Housing	Akulon S223
Approval and Application	
Approval Marks	CE marking ENEC certificate
Product Data	
Full product code	872790087764900
Order product name	SN 57
EAN/UPC - Product	8711500998576
Order code	913710010616
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	48
Material Nr. (12NC)	913710010616
Net Weight (Piece)	0.049 kg

Electronic semi-parallel ignitor for HID lamp circuits

Dimensional drawing



Product	C1	A1	A2	B1
SN 57	38.5 mm	85.5 mm	65.0 mm	41.5 mm

SN 57

