# WebService:

10/02/2019



## Picture

### Article

### 632.3500-000

BLOCK 3 DISTRIBUTION BOARD WITH CUTOUTS

Master data



| TechData                |                   |  |  |  |
|-------------------------|-------------------|--|--|--|
| Commercial series       | BLOCK Series      |  |  |  |
| Synthetical description | MODULAR ENCLOSURE |  |  |  |
| Mounting version        | SURFACE MOUNTING  |  |  |  |
| Protection degree       | IP66              |  |  |  |
| Protection degree<br>IK | IK08              |  |  |  |
| Dimensions              | 136x440x105mm     |  |  |  |

1 NR

1.159 KG

85381000

8001636030227



Minimum order

Harmonized System Code

Net Weight

EAN code

(HSCode)

UE Declaration of conformity



I.M.Q. Istituto Italiano del Marchio di Qualità

| Packaging    |               |  |  |  |
|--------------|---------------|--|--|--|
| Description  | Carton        |  |  |  |
| Quantity     | 4             |  |  |  |
| EAN code     | 8001636753522 |  |  |  |
| Gross weight | 5.256 KG      |  |  |  |

## **Approvals and Certifications**



Dissipable power

EN 60670-1 (2005) [European Standard] Boxes and enclosures for electrical accessories for household and similar fixed electrical installations. General requirements

**Standards and Laws** 

9W

EN 60670-24 (2013) [European Standard] Boxes and enclosures for electrical accessories for household and similar fixed electrical installations - Part 24: Particular requirements for enclosures for housing protective devices and other power dissipating electrical equipment

## Annexed



Instruction manual

# SCAME PARRE S.p.A. VIA COSTA ERTA, 15 24020 PARRE (BG) ITALY TEL. +39 035 705000 - TELEFAX +39 035 703122

# WebService:

10/02/2019



| Volume     | 36800 CCM        | Technical drawing [DWG] |
|------------|------------------|-------------------------|
| Dimensions | 320x460x250 (MM) | .chwg                   |
|            |                  | Technical drawing [PDF] |
|            |                  | Technical drawing [STP] |
|            |                  |                         |

|   |   | Note: |  |
|---|---|-------|--|
| > | (*) Cut-outs suitable for 32A socket outlets with 84x106 mm flange          | ×     |  |
| > | 70x87mm cut-outs  | ×     |  |
| > | Power dissipation calculated in conformity with CEI 23-49 italian standards | ×     |  |