

# ARDY

## BX-FLEX CONNECTORS SQUEEZE TYPE

ZINC DIE CAST

TOPAZ  
CAT # UPC# CONDUIT SIZE UNIT CTN SHIP CASE WT/ CASE

### 45° ANGLE

390 13670 3/8" 1/2" KO 50 500 45

### 90° ANGLE

100 10340 3/8" 1/2" KO 50 500 45

101 10350 1/2" 25 250 35

102 10360 3/4" 10 100 20

103 10370 1" 5 50 19

104 10380 1 1/4" 10 40 20

105 10390 1 1/2" -- 5 5

106 10400 2" -- 5 6

107 10410 2 1/2" -- 5 18

108 10420 3" -- 2 9

109 10430 3 1/2" -- 1 9

110 10440 4" -- 1 10

### INSULATED THROAT

100i 10341 3/8" 1/2" KO 50 500 45

101i 10351 1/2" 25 250 35

102i 10361 3/4" 10 100 20

103i 10371 1" 5 50 19

104i 10381 1 1/4" 10 40 20

105i 10391 1 1/2" -- 5 5

106i 10401 2" -- 5 6

### 90° ANGLE

MALLEABLE IRON

101M 10510 1/2" 25 250 40

102M 10520 3/4" 10 100 30

103M 10530 1" 5 50 30

104M 10540 1 1/4" -- 50 38

105M 10550 1 1/2" -- 5 5

106M 10560 2" -- 5 10

107M 10570 2 1/2" -- 5 16

108M 10580 3" -- 2 9

109M 10590 3 1/2" -- 1 14

110M 10600 4" -- 1 24

### INSULATED THROAT

101Mi 10511 1/2" 25 250 16

102Mi 10521 3/4" 10 100 30

103Mi 10531 1" 5 50 60

104Mi 10541 1 1/4" 5 50 76

105Mi 10551 1 1/2" -- 5 100


106Mi 10561 2" -- 5 200

107Mi 10571 2 1/2" -- 5 320


108Mi 10581 3" -- 2 450

109Mi 10591 3 1/2" -- 1 1400

110Mi 10601 4" -- 1 2400



CAT.#	A	B	C
390	1.588	1.132	.382



CAT.# A B (Min-Max) C SCREWS

100/i	1.740	0.43-0.72	.370	2
101/i	2.110	0.44-1.03	.400	2
102/i	2.400	0.76-1.15	.400	2
103/i	2.870	1.09-1.73	.540	2
104/i	4.000	1.34-1.97	.640	2
105/i	6.000	1.65-2.61	.750	2
106/i	6.000	1.54-2.54	.740	2
107	7.187	2.45-2.98	.875	4
108	7.875	2.93-3.45	1.031	4
109	9.400	3.28-3.95	1.031	4
110	10.200	3.68-4.43	1.031	4
101M	1.750	0.78-0.95	.440	2
102M	1.810	0.91-1.02	.440	2
103M	2.060	1.25-1.38	.560	2
104M	2.810	1.41-1.63	.560	2
105M	3.810	1.75-2.00	.560	2
106M	4.750	2.19-2.44	.690	2
107M	6.250	2.75-3.00	.880	4
108M	7.250	3.25-3.50	1.000	4
109M	10.250	3.70-4.16	1.250	4
110M	13.000	4.11-4.56	1.250	4
101Mi	1.750	0.78-0.95	.440	2
102Mi	1.810	0.91-1.02	.440	2
103Mi	2.060	1.25-1.38	.560	2
104Mi	2.810	1.41-1.63	.560	2
105Mi	3.810	1.75-2.00	.560	2
106Mi	4.750	2.19-2.44	.690	4
107Mi	6.250	2.75-3.00	.880	4
108Mi	7.250	3.25-3.50	1.000	4
109Mi	10.250	3.70-4.16	1.250	4
110Mi	13.000	4.11-4.56	1.250	4



SP®  
E148716



SP®  
E26493  
E148716  
E170258



SP®



SP®

BX-FLEX