
520PV





UPC Code: 07847784188

Country of Origin: Mexico - *Eligible for ARRA funded projects > \$7,443,000





Straight Blade Wiring Devices

Brand Features

Leviton offers a large selection of 15, 20, 30 and 50 Amp Commercial Grade Straight Blade Plugs and Connectors, available in a wide variety of features. These rugged performers are moisture, chemical and abuse-resistant, And they're ideal for indoor and outdoor use. Our EPTR rubber-backed plugs and connectors stand up to rough use, protecting against dirt and moisture. The deep-slotted, backed-out terminal screws draw backwire clamps securely over stripped leads for maximum conductivity.

Item Description

20 Amp, 125 Volt, NEMA 5-20P, 2P, 3W, Plug, Straight Blade, Commercial Grade, , Grounding - Yellow

Technical Information

Electrical Specifications Grounding: Grounding

Amperage: 20 Amp

Voltage: 125 Volt NEMA: 5-20P

Pole: 2

Wire: 3

Dielectric Voltage: Withstands 2000V per UL498

Current Interrupting: Certified for current interrupting at full rated current

Temperature Rise: Max 30C after 50 cycles OL at 150 percent rated current

Environmental Specifications Flammability: Rated V-2 per UL94 Operating Temperature: -40C to 60C Material Specifications Body Material: PVC Blades/Contacts: Brass Assembly Screws: Steel, Zinc Plated Color: Yellow

Mechanical Specifications Terminal ID: Brass-Hot, Green-Ground, Silver-Neutral

Terminal Accom.: 18-12 AWG Product ID: Ratings and NEMA I.D. permanently marked on device Cord Range: .245 - .700

Product Features NEMA: 5-20P Color: Yellow

Standards and Certifications

NEMA: WD-6 ANSI: C-73 UL498: File E13393 CSA C22.2 No. 42: File LR-406 NOM: 057 Warranty: 10-Year Limited



