

14W47





UPC Code: 07847784829

Country of Origin: United States - *Eligible for ARRA funded projects







Watertight and Dust-tight Devices

Brand Features

Leviton's Wetguard line of industrial watertight wiring devices are the most versatile, well-engineered watertight devices on the market. They meet IP67 and NEMA ratings for water ingress protection, and offer many significant advantages over competitive

Item Description

15 Amp, 125 Volt, NEMA 5-15P, 2P, 3W, Plug, Straight Blade, Industrial Grade, Grounding, Wetguard - YELLOW

Technical Information

Electrical Specifications Mechanical Specifications

Terminal ID: Brass-Hot, Green-Ground, **Grounding:** Grounding

Amperage: 15 Amp

Voltage: 125 Volt Pole: 2 permanently marked on device

Wire: 3 Dielectric Voltage: Withstands 2000V per

Current Limiting: Full Rated Current

Temperature Rise: Max 30C after 250 cycles OL at 200 percent rated current

Environmental Specifications

Flammability: Rated V-2 per UL94

Operating Temperature: -40C to 60C

Material Specifications

Body Material: Santoprene TPV

Compression Nut, Strain Relief: Nylon

Wire Module: Nylon **Bushing:** Santoprene TPV

Blades/Contacts: Electroless Nickel-

coated Brass

Terminal Screws: Electroless Nickel-

coated Brass

Assembly Screws: Stainless Steel, Non-

Magnetic

Silver-Neutral

Terminal Accom.: 18-10 AWG Product ID: Ratings and NEMA I.D.

Cord Grip Range (in): .234-.687

Cord Range: .375 - .655

Product Features

NEMA: 5-15P Color: Yellow

Standards and Certifications

NEMA: WD-6 **ANSI:** C-73 **UL**: 498

CSA C22.2 No. 42: File LR-406

NOM: 057

Warranty: Lifetime Warranty

Dimensional Diagram





