

Condulet® Single Gang Cast Device Boxes

Accessories Pages 35 to 44

3F

With and Without Mounting Lugs for Threaded Rigid and IMC Conduit

Application:

Cast device boxes are installed to:

- accommodate wiring devices
- act as pull boxes for conductors in a conduit system
- provide openings to make splices and taps in conductors
- provide access to conductors for maintenance and future system changes
- connect conduit sections
- FSF boxes for mounting surface devices on floor or bench (used with single gang covers)

Features:

- Internal green ground screw standard on boxes
- Suitable for use in wet locations when used with gasketed covers
- Mounting lugs standard on most boxes
- Tapered threaded hubs (NPT) with integral bushing
- Available for surface mounting (with mounting lugs) or flush mounting (without mounting lugs) as listed
- Available as shallow (FS) or deep (FD) configuration. Use FD if device to be enclosed exceeds 1 5/8" in depth
- Ample wiring room provided in either FS or FD configuration
- Wide selection of surface or flush covers available in three materials (sheet steel, *Feraloy*®, aluminum)
- Covers for flush mounting extend to conceal the rough plaster line
- Available in single gang and multi-gang configurations with hubs, and as blank bodies for drilled and tapped openings

Standard Materials:

- *Feraloy* iron alloy or copper-free aluminum.

Standard Finishes:

- *Feraloy* – electrogalvanized and aluminum acrylic paint
- Aluminum – natural

Options:

- Finishes:
 - *Corro-free*™ epoxy powder coat – add suffix S752

Size Ranges:

- Hubs – 1/2" to 1"

Certifications and Compliances:

- UL Standard: 514
- ANSI Standard: C33.84
- Fed. Spec.: W-C-5860
- CSA Standard: C22.2 No. 18



FS & FD

Size	Cat. #	Cat. #
1/2	FS1*	FD1**
3/4	FS2*	FD2**
1	FS3**	FD3**



Size	Cat. #	Cat. #
1/2	FSC1*	FDC1**
3/4	FSC2*	FDC2**
1	FSC3**	FDC3**

Size	Cat. #	Cat. #
1/2	FSL1	FDL1
3/4	FSL2	FDL2**

Die Cast Aluminum†

Size	Cat. #	Cat. #
1/2	FS1-SA	FSC1-SA
3/4	FS2-SA	FSC2-SA

† Mounting lugs and ground screw are not offered with standard die cast box – add suffix SCA to Cat. No. for sand cast aluminum box with mounting lugs and ground screw. (Example: FS1-SCA)

* Available in sandcast copper-free aluminum – add suffix SCA to Cat. No.

** Available in sandcast copper-free aluminum – add suffix SA to Cat. No.

3F Cast Device Boxes