
# 2310





UPC Code: 07847780110





# **Locking Wiring Devices**

#### Brand Features

Leviton's Industrial Grade Locking Devices are built to provide unparalleled quality and superior performance in the most severe industrial settings. Leviton combines the best materials available with superior production standards to produce a broad selection of Locking Devices of unmatched flexibility and dependability.

### **Item Description**

20 Amp, 125 Volt, NEMA L5-20R, 2P, 3W, Flush Mtg Locking Receptacle, Industrial Grade, Grounding, V-0-MAX - BLACK

#### **Technical Information**

AC Horsepower Ratings Horsepower Rating: 1 HP

**Electrical Specifications** 

Grounding: Grounding

Amperage: 20 Amp

Voltage: 125 Volt NEMA: L5-20R

Pole: 2

Wire: 3

Dielectric Voltage: Withstands 2000V per UL498

Current Limiting: Full Rated Current Temperature Rise: Max 30C after 250 cycles OL at 200 percent rated current

## Environmental Specifications Flammability: Rated V-0 per UL94

Operating Temperature: -40C to 60C

### Material Specifications

Face Material: Ultramid Base Material: Valox Line Contacts: Brass .040 Thick Terminal Screws: Brass 10-32 Grounding Screw: Brass 8-32 Yoke: Nickel-Plated Brass .050 Thick Strap Material: Nickel-Plated Brass Color: Black Mechanical Specifications

**Terminal ID:** Brass-Hot, Green-Ground, Silver-Neutral

Terminal Accom.: 14-8 AWG

Product ID: Ratings and NEMA I.D. permanently marked on device Termination: Back & Side

Product Features **NEMA:** L5-20R

Color: Black

Standards and Certifications NEMA: WD-6 ANSI: C-73 UL498: File E13399 UL Fed Spec WC-596: File E13399 CSA C22.2 No. 42: File LR-406 NOM: 057 Warranty: Lifetime Warranty

ces

LEVITON

