



INDUSTRIAL
COMMERCIAL

E-39 LOCKING DEVICES

TESTING & CODE COMPLIANCE

- Listed to UL 498 Receptacles: (file no. E15058); UL verified to Federal Spec. WC-596;
- Plugs & Connectors: (file no. E15012).
- CSA Certified to C22.2 no. 42. Receptacles: (file no. LR6914 (6233-01)), Plugs & Connectors: (file no. LR2081 (6221-02)).
- NOM Certified, except as noted.

MATERIAL CHARACTERISTICS


- Receptacles: Nylon.
- Plugs, Connectors: Polycarbonate.
- Meets flammability requirements per UL 94, V2 rated.
- Temperature Rating: Receptacles: -40°C to 70°C. Plugs & Connectors: -20°C to 60°C.




Commercial Specification Grade Locking Devices

3 Pole, 4 Wire Grounding
NEMA L14-30, 30A 125/250V
NEMA L15-30, 30A 250V 3Ø
NEMA L16-30, 30A 480V 3Ø
NEMA L17-30, 30A 600V 3Ø

30A 3 Pole, 4 Wire Commercial Specification Grade Receptacles



L1430R



L1630R



L1430P

FEATURES

- Rugged nylon face and body.
- Clearly marked rating, NEMA configuration and approval listings on receptacle face.
- One piece brass contacts offer superior performance and minimum heat rise.
- Back wire terminal clamps for easy secure wiring.
- Combination head screws standard - slot/Phillips in the U.S.

Commercial Specification Grade Receptacles

Rating					
A	V/AC	NEMA	Description	Color	Catalog No.
30	125/250	L14-30	Single	Black	L1430R
30	250V 3Ø	L15-30	Single	Black	L1530R
30	480V 3Ø	L16-30	Single	Black	L1630R*
30	600V 3Ø	L17-30	Single	Black	L1730R*

*Not NOM

30A 3 Pole, 4 Wire Commercial Specification Grade Locking Plugs and Connectors

FEATURES

- Abuse resistant thermoplastic construction.
- Back wire Dead-Front design.
- External cable clamp provides firm strain relief.
- Back wire terminal clamps for easy secure wiring.
- Individual wiring compartments with tapered channel for easy insertion of wires.
- Triple combination head screws standard - slot/Phillips/Robertson for use in the U.S. and Canada.
- Clear cover over wiring compartments allow easy inspection of wiring terminations.
- Clearly marked rating, NEMA configuration and standard compliances on face of plug or connector.

Commercial Specification Grade Locking Plugs and Connectors

Rating					Catalog No.	
A	V/AC	NEMA	Description/ Cord Diameter	Color	Plug	Connector
30	125/250	L14-30	Straight: 0.25"-0.69" (6.35mm-17.5mm)	Black & White	L1430P	L1430C
30	250V 3Ø	L15-30	Straight: 0.25"-0.69" (6.35mm-17.5mm)	Black & White	L1530P	L1530C
30	480V 3Ø	L16-30	Straight: 0.25"-0.69" (6.35mm-17.5mm)	Black & White	L1630P	L1630C

NOTE: Weather Protective Covers from Cooper Wiring Devices that may be used with these products are described on pages E-71 in this section.

