

Avvisatori acustici industriali

Industrial horns


V 12-24-48-110-240 (±10%)		~ 50/60 Hz	On ∞	autoestinguente self-extinguishing
IP 65			Hz 300÷350	°C -30 +40



Suono continuo Single sound

V ~	12	24	48	110	240
mA	830	415	210	90	42
dB(A)1m	95	95	95	95	95

MS12A	53002	MS110A	53008
MS24A	53003	MS240A	53015
MS48A	53005		




Kg. 0,31



Suono intermittente Intermittent sound

V ~	12	24	48	110	240
mA	850	430	220	95	45
dB(A)1m	95	95	95	95	95

MSSI12A	53530	MSSI110A	53533
MSSI24A	53531	MSSI240A	53535
MSSI48A	53532		




Kg. 0,38



Suono continuo Single sound

V ~	12	24	48	110	240
mA	830	415	210	90	42
dB(A)1m	95	95	95	95	95

MSSD12A	53050	MSSD110A	53054
MSSD24A	53051	MSSD240A	53057
MSSD48A	53053		




Kg. 0,33



Suono intermittente Intermittent sound

V ~	12	24	48	110	240
mA	850	430	220	95	45
dB(A)1m	95	95	95	95	95

MSSDSI12A	53551	MSSDSI110A	53554
MSSDSI24A	53552	MSSDSI240A	53556
MSSDSI48A	53553		



Kg. 0,39



Suono continuo Single sound


V ~	12	24	48	110	240
mA	830	415	210	90	42
dB(A)1m	95	95	95	95	95

MSR12A	53537	MSR110A	53540
MSR24A	53538	MSR240A	53542
MSR48A	53539		

Suono intermittente Intermittent sound

V ~	12	24	48	110	240
mA	850	430	220	95	45
dB(A)1m	95	95	95	95	95

MSRSI12A	53544	MSRSI110A	53547
MSRSI24A	53545	MSRSI240A	53549
MSRSI48A	53546		



Kg. 0,42



Suono continuo Single sound


V ~	12	24	48	110	240
mA	830	415	210	90	42
dB(A)1m	95	95	95	95	95

MSSDR12A	53558	MSSDR110A	53561
MSSDR24A	53559	MSSDR240A	53563
MSSDR48A	53560		

Suono intermittente Intermittent sound

V ~	12	24	48	110	240
mA	850	430	220	95	45
dB(A)1m	95	95	95	95	95

MSSDRSI12A	53565	MSSDRSI110A	53568
MSSDRSI24A	53566	MSSDRSI240A	53570
MSSDRSI48A	53567		



Kg. 0,42

Per ordinare l'opzione nera vedere codici su listino in vigore. Black option available on request.