

Sirene elettroniche

Electronic sirens

$V_{12\div 24}$  -48 $\sim$ -110 $\sim$ -240 $\sim$ ($\pm 10\%$)		$\sim$ 50/60 Hz	On ∞
autoestinguente self-extinguishing	IP 30		
			$^{\circ}\text{C}$ -30 +50




SE 4/29 MS 5
SE429MS5

(B)

V_{DC}	12÷24	-	-	-
V_{AC}		48	110	240
mA	350 370	130	55	36
dB(A)1m	Min 86.5 - Max 97			IP 30

SE429MS51224DA	50415
SE429MS548A	50416
SE429MS5110A	50417
SE429MS5240A	50418



Kg. 0,60



SE 10/32 MS 5
SE1032MS5

(B)

V_{DC}	12÷24	-	-	-
V_{AC}		48	110	240
mA	370 400	120	55	25
dB(A)1m	Min 88.5 - Max 99.5			IP 30

SE1032MS51224DA	50419
SE1032MS548A	50420
SE1032MS5110A	50421
SE1032MS5240A	50422



Kg. 1,00




SE 4/25 L PLC
SE425LPLC

(B)

V_{DC}	24
mA	120
dB(A)1m	93
	IP 30

SE425LPLC24D	50414
--------------	-------



Kg. 0,30



SE 10/32 MS 5 PLC
SE1032MS5PLC

(B)

V_{DC}	24
mA	370
dB(A)1m	Min 93 - Max 96.5
	IP 30

SE1032MS5PLC24D	50423
-----------------	-------



Kg. 0,60