

Article

623.3006-062
 3-WAY ADAPTOR IP44

Picture**Master data**

Minimum order	1 NR
Net Weight	1.739 KG
EAN code	8001636037868
Harmonized System Code (HSCode)	85366990

TechData

Commercial series	ADAPTO Series
Synthetical description	MULTI -WAY ADAPTOR
Protection degree IP	IP44
Inlet supply unit	Direct supply to main switch
No. of available outlets	3
No. of sockets 2P +E 16A	3
In disp. ing/tipo apparecchio	MCB 2P 16A
In disp. ing/tipo apparecchio	RCD 2P 25A 0,03A
Max power	3 KW

Approvals and Certifications

UE
 Declaration of conformity



EAC
 Eurasian Conformity

Standards and Laws

IEC/TS 61439-7 (2014-02)
 [International Standard] Low-voltage switchgear and controlgear assemblies - Part 7: Assemblies for specific applications such as: marinas, camping sites, market squares, electric vehicles charging stations.

Packaging

Description	Carton
Quantity	1
EAN code	8001636931999
Gross weight	2.236 KG

Annexed

Wiring diagram

Volume	15840 CCM
Dimensions	275x320x180 (MM)

Note:

> Zinc-plated steel carrying handle.



> Equipped with PG21 cable gland, cable clamp and terminal block.

**Technical Details**

2P+E	Poles
ADAPTO Series	Commercial series
Stationary distrib.assemblies	Typology
16A	Rated current
Direct supply to main switch	Inlet supply unit
AC	Type of current
IP44	Protection degree
IEC/TS 61439-7 (2014-02)	Reference standard
Not applicable	Emergency push button
Main switch with RCD	RCD protection
MCB 2P 16A	Device supply unit
RCD 2P 25A 0,03A	Device supply unit
3 KW	Max power
CEILING MOUNTING	Mounting version
230V	Rated voltage
Without cable and plug	Version

Wiring diagram