

PVC-Coated Conduit and Accessories

Corrosion-protected connections for conduit sections.

Ocal-Blue® Couplings




- Nominal .002" (2 mil) blue urethane coating on interior and threads
- Minimum .040" (40 mil) PVC coating bonded to exterior — in your choice of blue, white, gray or custom colors
- Straight threads (NPS)
- Molded ribs on outer coating for easy installation (up to and including 4" trade size)
- Pressure-sealing sleeves protect your connection



CAT. NO.		COUPLING SIZE IN. METRIC SIZE DESIGNATOR*	MIN. LENGTH OF METAL IN. MM	TOTAL MIN. LENGTH INCLUDING SLEEVE IN. MM	WEIGHT STEEL ONLY LBS. KG
STEEL	ALUMINUM				
CPL1/2-	CPL1/2SA-	½ 16	1.50 38.10	3.75 95.25	.13 .06
CPL3/4-	CPL3/4SA-	¾ 21	1.53 38.91	3.75 95.25	.19 0.85
CPL1-	CPL1SA-	1 27	1.91 48.41	4.94 139.70	0.33 .15
CPL1-1/4-	CPL1-1/4SA-	1¼ 35	1.91 48.41	5.50 139.70	0.43 .19
CPL1-1/2-	CPL1-1/2SA-	1½ 41	1.91 48.41	5.75 146.05	0.56 .25
CPL2-	CPL2SA-	2 53	1.94 49.19	5.94 150.79	0.77 .35
CPL2-1/2-	CPL2-1/2SA-	2½ 63	2.88 73.10	6.88 174.70	1.85 .83
CPL3-	CPL3SA-	3 78	3.03 76.98	7.03 178.58	2.70 1.22
CPL3-1/2-	CPL3-1/2SA-	3½ 91	3.09 78.58	7.09 180.18	3.78 1.70
CPL4-	CPL4SA-	4 103	3.19 80.97	7.19 182.57	3.08 1.39
CPL5-	CPL5SA-	5 129	3.37 85.69	7.37 187.29	5.00 2.25
CPL6-	CPL6SA-	6 155	3.44 87.29	7.44 188.89	8.00 3.60

Note — Inches and pounds are indicated in bold type. Metric measure is directly below bold type.

* Metric size designator (ANSI C80.1-1994).

CAT. NO.	SIZE	MATERIAL	COLOR
CPL1	SA-		
		Blank = Steel	_ = space for color identifier
		SA = Aluminum	G = Gray 
			W = White 
			B = Blue 
Catalog No. Example: CPL1SA-B is a 1" aluminum coupling coated in blue PVC.			
Custom colors also available.			

United States
Tel: 901.252.8000
800.816.7809
Fax: 901.252.1354

Technical Services
Tel: 888.862.3289

Thomas & Betts
A Member of the ABB Group