Thomas@Betts







Actual

Catalog Number: X27-G

 Product ID:
 7TAA087200R0038

 UPC Number:
 70450841529

Status:

PVC Coated Conduit Body, X Type, Form 7, Size 3/4 Inch/21 Metric, Iron, Dark Gray

- A minimum of .040 inch PVC coating is bonded to the exterior.
- Covers are coated with a molded flange to seal the conduit body while the conduit body is molded with a flat surface on its opening to seal with the cover.
- · Ocal pressure-sealing sleeves on all threaded hubs.
- Ocal conduit bodies are shipped with a cover and encapsulated stainless steel screws.
- Bodies are designed with a flat back, allowing more cubic inch capacity. The flat back also keeps the body more stable during installation, requiring fewer conduit straps.
- Provide openings for making splices and taps in conductors
- · Connect conduit sections
- · Provide taps for branch conduit runs
- · Make 90° bends in conduit runs
- · Provide for access to conductors for maintenance and future system changes

North American Specifications (UNSPSC)	
UNSPSC	39131708 Electrical conduit fitting body
IGCC	5563 Electrical conduit fitting body
Туре	Form 7 Conduit Body
Special Features	The Conduit Body and Cover are Double Coated
	with a Nominal .002 In. Blue Urethane on Both The
	Interior and Exterior, Before PVC Coating is Applied
Application	Act As Pull Outlets for Conductors Being Installed
Standard	UL E2969
Hub Size	3/4 in ; 21 mm
Form	Form 7
Material	Iron
Finish	PVC Coated
Color	Dark Gray

Packaging	
Outer Quantity	10
Outer Dimensions (inches)	15.35x13.8x8.35
Weight Uom	2.51 lbs. Each

Documents / Support Tools	
Technical Drawing / Data Sheet US	Available on Website
Support/Tools	Available on Website
Catalog US	Available on Website

For further technical assistance, please contact us...

ABB Installation Products - USA 860 Ridge Lake Blvd. Memphis, TN 38120 www.tnb.com ABB Installation Products Technical Support MS 3B-50 860 Ridge Lake Blvd. Memphis, TN 38120 Hours: 7AM - 6PM CDT Monday-Friday Phone: (888) 862-3289 Fax: (901) 252-1321 Email:techsupport@tnb.com