


Box Label (120mm x 50mm): JBL-54038
 EX marks: EX eb IIC T4 Gb/ Ex tb III C T130 Db
 Intended use: Can be used in zone 1 and zone 2
 Can be used in zone 21 and zone 22.
 Degree of protection: IP66
 Rated voltage/current: 220V
 Rated current: 16A
 Ambient temperature use: -40 ~ +55°C
 Material of enclosure: 316 L Stainless steel.
 Thickness: 2mm
 Earthing: M6
 With an enclosure: 510mm*510mm*226mm.
 With 123*2.5mm² phoenix terminals:
 Three slotted canal duct of 40 mm x 60 mm (W X H)
 on each side of the
 With 34 pcs cable entry holes dia21.5mm . 1pc dia27mm, 2pc dia33.5mm at bottom
 Open type: Door-open type

Customer			Approve sign				http: www.cz-ex.com e-mail: czwd@cz-ex.com	Product Name	Stainless steel explosion-proof junction box	
Service			Date					Product Code	CZ1320/6260-510*510*226-123*UK3N/ X34-21.5/X1-27/X2-33.5+4036/6	
Designer	GUO	Date	2019.6.5			Quantity	Sets			
Audit	YE	Recheck				Unit: mm	DWG# 20190605G002			

1 2 3 4 5 6 7 8

F E D C B A