



Box Label (120mm x 50mm): JBP-254010
 EX marks: EX eb IIC T4 Gb/ Ex tb III C T130 Db
 Intended use: Can be used in zone 1 and zone 2
 Can be used in zone 21 and zone 22.
 Degree of protection: IP66
 Rated voltage/current: 220V
 Rated current: 16A
 Ambient temperature use: -40 ~ +55°C
 Material of enclosure: 316 L Stainless steel.
 Thickness: 2mm
 Earthing: M6
 With an enclosure: 510mm*510mm*226mm.
 With 100*2.5mm² phoenix terminals:
 Three slotted canal duct of 40 mm x 60 mm (W X H)
 on each side of the
 With cable entry holes: 32 pos dia 21.5mm, 2 pos 27mm, 1pc 33.5mm at bottom
 Open type: Door-open type

Customer			Approve sign				http: www.cz-ex.com e-mail: czwd@cz-ex.com	Product Name	Stainless steel explosion-proof junction box	
Service			Date					Product Code	CZ1320/6260-510*510*226-100*UK3N/X32-21.5mm/X2-27mm/X1-33.5mm+4036/6	
Designer	GUO	Date	2019.6.5			Quantity	Sets			
Audit	YE	Recheck				Unit: mm	Page 1 of 1			
						DWG#	20190605G004			