






Box Label (120mm x 50mm): JBS-253510
 EX marks: EX eb IIC T4 Gb/ Ex tb IIIC T130 Db
 Intended use: Can be used in zone 1 and zone 2
 Can be used in zone 21 and zone 22.
 Degree of protection: IP66
 Rated voltage/current: 220V
 Rated current: 16A
 Ambient temperature use: -40 ~ +55℃
 Material of enclosure: 316 L Stainless steel.
 Thickness: 2mm
 Earthing: M6
 With a enclosure: 510mm*510mm*226mm.
 With 100*2.5mm² phoenix terminals:
 Three slotted canal duct of 40 mm x 60 mm (W X H)
 on each side of the
 With cable entry holes 32 pos dia 21.5mm, 2 pos 27mm, 1pc 33.5at bottom
 Open type: Door-open type



Customer		Approve sign						Product Name Stainless steel explosion-proof junction box Product Code CZ1320/6260-510*510*226-100*UK3N/X32-21.5mm/X2-27mm/X1-33.5mm+4036/6 Quantity Sets DWG# 20190605G005	
Service		Date							
Designer	GUO	Date	2019.6.5						
Audit	YE	Recheck							
				http: www.cz-ex.com e-mail: czwd@cz-ex.com				Page 1 of 1	