



Smartbright Waterproof G3 WT068C

WT068C CW LED36 L1200 PSU

New Smartbright Waterproof Batten G3 provide flexibility to customer to choose from 3 sizes, standard and through wiring version and 2 CCTs to cater to different customer needs

Product data

General Information	
Light source color	865 cool daylight
Optical cover/lens type	-
Control interface	-
Protection class IEC	Safety class II
CE mark	CE mark
Number of products on MCB of 16 A type B 1	
Light source engine type	LED
Operating and Electrical	
Input Voltage	220 to 240 V
Input Frequency	50 or 60 Hz
Power Factor (Min)	0.9

Controls and Dimming	
Dimmable	No
Mechanical and Housing	
Housing Material	Polycarbonate
Optical cover/lens material	Polycarbonate
Optical cover/lens finish	Opal
Overall length	1188 mm
Overall width	69 mm
Overall height	74 mm
Color	White and gray
Approval and Application	
Ingress protection code	IP66 [Dust penetration-protected, jet-proof]

Smartbright Waterproof G3 WT068C

Mech. impact protection code	IK06 [1 J]
------------------------------	-------------

Initial Performance (IEC Compliant)


Initial luminous flux (system flux)	3600 lm
Luminous flux tolerance	+/-10%
Initial LED luminaire efficacy	110 lm/W
Init. Corr. Color Temperature	6500 K
Init. Color Rendering Index	>80
Initial input power	33 W
Power consumption tolerance	+/-10%

Application Conditions

Ambient temperature range	-20 to +45 °C
---------------------------	---------------


Product Data

Full product code	871016336060799
Order product name	WT068C CW LED36 L1200 PSU
EAN/UPC - Product	8710163360607
Order code	911401881480
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	12
Material Nr. (12NC)	911401881480
Net Weight (Piece)	0.490 kg



Dimensional drawing

WT068C-4ft



Dust/ water protected LED

