



Technical Data

Document Reference

20/03653R1

UL 13



UL Listed

PLTC

RAMCROii - INSTRUMENTATION Cable

For standard applications, low smoke, Halogen Free

Multi-Pair, XLPE-Insulation, Individual & Collective Screen, LSZH-Sheath

Code: MAC0405HEEXN-UL13CC

XLPE/IAM/CAM/LSZH

Application

These cables are designed to connect electronic instrumentation, analog and digital signal circuits. This cable does not spread flame to the top of the tray in the Vertical-Tray Flame Test in UL 1685.

Construction		4x2x18AWG + COMM CORE	
Formation	4 Pairs	Unit	Nominal Value
Section	18AWG		
Conductor	Plain annealed copper wire, 7 strand	mm	1,2
Insulation	Cross Linked Polyethylene - XLPE	mm	2,0
Colour Code	White, Black + Numbered Tapes		
Individual Screen	0,026 mm Aluminium / PETP tape over tinned copper drain wire		
Wrapping	at least 1 layer of plastic tape 0,023 mm		
Collective Screen	0,026 mm Aluminium / PETP tape over tinned copper drain wire		
Inner Sheath	N.A.		
Armour	N.A.		
Outer Sheath	Thermoplastic Low Smoke, Halogen Free - LSZH - Black	mm	14,3
Cable Printing	RAMCRO S.p.A. - (UL) Listed E345186 Type PLTC - 4 pr 18 - Shielded - 75°C + BATCH + METER MARKING		

Technical Data & Standard References

Fire Propagation:		Construction Reference Standard:	UL 13
- Test on single cable	IEC 60332-1	Type of Cable:	PLTC Cable
- Test on bunched cables	IEC 60332-3	Low Voltage Directive	2014/35/UE
- Vertical Tray Flame Test	UL1685	Other References:	
Limiting Oxygen Index (LOI)	(min 37%)	- NEC code, sec. 725 PLTC,	
Smoke Density	IEC 61034	- NEC code, sec. 727 ITC,	
Amount of halogen acid gas	IEC 60754-1 (max 0,5%)	- UL 1685	
Acidity (ph value) and conductivity	IEC 60754-2	- ASTM D 1239	
Notes		- NF C 32-020	
		- IRAM IAP	

Electrical & Mechanical Data

Conductor Cross-section	Nom.	18AWG	Temperature Range:	
DC Resistance per core at 20° C	max	Ω/km	23,8	During Installation
Insulation Resistance at 20° C	min	MΩ*km	1000	Fixed Installation
Mutual Capacitance	max	nF/km	75	Insulation Operation
Inductance	max	mH/km	1	Min. Bending Radius
Test Voltage - Core/Core	V	2000	Max Pulling Tension	N/mm2
Test Voltage - Core/Screen	V	2000	Weight Approx	kg/km
L/R Ratio	max	μH/Ω	40	
Operating Voltage	V	300		



Issued by: DEBORAC_PMS

Prepared by RAMCRO Tech

Creator: LDG

Via Marzorati, 15 - 20014 Nerviano - Milan - Italy / www.ramcro.it

Transfer to third parties only under authorization by Ramcro S.p.A.

Printing errors excepted. Subject to alterations.



Date of issue:

20/10/2020 14:28

NEW Form 2