



SmartBright Solar Allin-One Streetlight

BRP110 LED 85/757

Integrated solar street light with Lithium Ferro Phosphate battery, solar panel and charger built into the luminaire. With light control and dimming function, automatic dusk to dawn operation, microwave sensor based movement detection and dim level adjustment luminaire effectively extends the working time. No wiring required and easy to install, no electricity cost and maintenance free.

Product data

Mechanical and Housing

Housing Material

| General Information | |
|----------------------------------|--------------------------------|
| Light source color | Cool white |
| Driver included | Yes |
| Optical cover/lens type | Polycarbonate cover |
| Operating and Electrical | |
| Battery type | Lithium Ferro Phosphate |
| Battery capacity | >530Wh |
| Battery voltage | 12.8 V |
| Panel type | Monocrystalline |
| Panel voltage | 18 Vmp |
| Panel peak wattage | 90 Wp |
| Charge controller type | MPPT (integrated) |
| Charger efficiency | >90% |
| Sensor Type | Microwave sensor |
| Controls and Dimming | |
| Dimmable | Yes |
| Configurability | Via handheld remote (optional) |
| Automatic Dusk to dawn detection | Yes |

| Overall length | 1485 mm |
|--|--------------------------------------|
| Overall width | 380 mm |
| Overall height | 95 mm |
| Color | Gray |
| | |
| Approval and Application | |
| Ingress protection code | IP65 |
| IK Rating | IK 08 |
| Autonomy | >24 hrs (with fully charged battery) |
| | |
| Initial Performance (IEC Compliant) | |
| Initial luminous flux (system flux) | 8500 lm |
| Initial LED luminaire efficacy | 140 lm/W |
| Init. Corr. Color Temperature | 5700 K |
| | |
| Init. Color Rendering Index | >70 |
| Init. Color Rendering Index Application Conditions | >70 |
| <u>-</u> | >70 0 to +45 °C |


Datasheet, 2020, July 10 data subject to change

Body: AL1060/stamping, Housing side frame: AL6063/extrusion, Bracket: CRSS/SPCC, Pole adaptor:AL6063/extrusion


SunStay

| Grid connection type | Off grid | |
|----------------------|------------------|--|
| Battery location | Inside Luminaire | |

Solar dimming profile



Dimensional drawing



Solar Street Lights



| Order product name | BRP110 LED85/757 |
|---------------------------------|------------------|
| Order product name | |
| Order code | 911401863781 |
| Numerator - Quantity Per Pack | 1 |
| Numerator - Packs per outer box | 1 |
| Material Nr. (12NC) | 911401863781 |
| Net Weight (Piece) | 19.65 kg |
| Net Weight (Piece) | 19.65 kg |



