



Technical Data

Document Reference

21/02710



UL 13

UL Listed

PLTC

RAMCROil - INSTRUMENTATION Cable

For standard applications, low smoke, Halogen Free

Multi-Pair, XLPE-Insulation, Individual & Collective Screen, LSZH-Sheath

Code: MAC0207HEEXN-UL13CC -- CU 21,3 kg/km

XLPE/IAM/CAM/LSZH

Application

These cables are designed to connect electronic instrumentation, analog and digital signal circuits. This cable does not spread flame to the top of the tray in the Vertical-Tray Flame Test in UL 1685.

Construction	2x2x22AWG + COMM CORE		
Formation	2 Pairs	Unit	Nominal Value
Section	22AWG		
Conductor	Plain annealed copper wire, 7 strand	mm	0,8
Insulation	Cross Linked Polyethylene - XLPE	mm	1,6
Colour Code	White, Black + Numbered Tapes		
Individual Screen	0,026 mm Aluminium / PETP tape over tinned copper drain wire		
Wrapping	at least 1 layer of plastic tape 0,023 mm		
Collective Screen	0,026 mm Aluminium / PETP tape over tinned copper drain wire		
Inner Sheath	N.A.		
Armour	N.A.		
Outer Sheath	Thermoplastic Low Smoke, Halogen Free - LSZH - Black	mm	7,7
Cable Printing	RAMCRO S.p.A. - (UL) Listed E345186 Type PLTC - 2 pr 22 - Shielded - 75°C + BATCH + METER MARKING		

Technical Data & Standard References

Fire Propagation:			
- Test on single cable	IEC 60332-1	Construction Reference Standard:	UL 13
- Test on bunched cables	IEC 60332-3	Type of Cable:	PLTC Cable
- Vertical Tray Flame Test	UL1685	Low Voltage Directive	2014/35/UE
Limiting Oxygen Index (LOI)	(min 37%)	Other References:	
Smoke Density	IEC 61034	- NEC code, sec. 725 PLTC,	
Amount of halogen acid gas	IEC 60754-1 (max 0,5%)	- NEC code, sec. 727 ITC,	
Acidity (ph value) and conductivity	IEC 60754-2	- UL 1685	
Notes		- ASTM D 1239	
-- CU 21,3 kg/km		- NF C 32-020	
		- IRAM IAP	

Electrical & Mechanical Data

Conductor Cross-section	Nom.	22AWG	Temperature Range:	
DC Resistance per core at 20° C	max Ω /km	70,7	During Installation	° C -5° C up to +50° C
Insulation Resistance at 20° C	min $M\Omega$ *km	1000	Fixed Installation	° C -40° C up to +75° C
Mutual Capacitance	max nF/km	75	Insulation Operation	-40° C up to +90° C
Inductance	max mH/km	1	Min. Bending Radius	mm 8 x cable diameter
Test Voltage - Core/Core	V	2000	Max Pulling Tension	N 69
Test Voltage - Core/Screen	V	2000	Weight Approx	kg/km 74
L/R Ratio	max $\mu H/\Omega$	25		
Operating Voltage	V	300		



Issued by: DEBORAC_PMS

Date of issue:

Prepared by RAMCRO Tech

Via Marzorati, 15 - 20014 Nerviano - Milan - Italy / www.ramcro.it

30/06/2021 11:38

Creator: LDG

Transfer to third parties only under authorization by Ramcro S.p.A.

NEW Form 2

Printing errors excepted. Subject to alterations.