

PRODUCT-DETAILS

3GBA111320-ADD

M2BAX 112MB 2



General Information

Product ID	3GBA111320-ADD
ABB Type Designation	M2BAX 112MB 2
Catalog Description	M2BAX 112MB 2

Additional Information

ABB Type Designation	M2BAX 112MB 2
Altitude	1000 m
Ambient Temperature	40 °C
Bearing	6206-2Z/C3
Bearing NDE	6205-2Z/C3
Country of Origin	China (CN)
Customs Tariff Number	85015220
Direction of Rotation	Both sides
Electrical Data	

Conn	Temp Class	Freq	Voltage	Power	Speed	Current	Power Factor	Efficiency	Torque	IS/IN
Y	--	50 Hz	690 V	4.00 kW	2908 r/min	4.13 A	0.920	88.10 %	13.13 N·m	9.60
D	--	50 Hz	400 V	4.00 kW	2909 r/min	7.12 A	0.920	88.10 %	13.13 N·m	9.60
Y	--	50 Hz	660 V	4.00 kW	2902 r/min	4.27 A	0.930	88.10 %	13.18 N·m	8.60
D	--	50 Hz	380 V	4.00 kW	2902 r/min	7.42 A	0.930	88.10 %	13.18 N·m	8.60
D	--	50 Hz	415 V	4.00 kW	2920 r/min	6.94 A	0.910	88.10 %	13.10 N·m	10.30

Gross Weight	47 kg
IC Class	IC411
IE Class Data (50 Hz)	IE Class IE3 Full Load (100%) 88.1 % Partial Load (75%) 88.5 % Partial Load (50%) 87.6 %
IE Class Data (60 Hz)	IE Class IE3 Full Load (100%) 88.5 % Partial Load (75%) 88.2 % Partial Load (50%) 86.7 %
IM Class	IMB3 IM1001
IP Class	IP55
Insulation Class	ICLF
Invoice Description	M2BAX 112MB 2
Made To Order	No
Minimum Order Quantity	1 piece
Number of Poles (High)	2
Order Multiple	1 piece
Package Level 1 Units	0 carton
Product Name	3-Phase squirrel cage motor
Product Net Weight	42 kg
Product Type	EBA3_M2BAX_CI
Quote Only	No
SCIP	d19446d4-4db6-4ddb-826d-2341a0f7dd46 Finland (FI)
Selling Unit of Measure	piece
Stocked At (Warehouses)	Menden, Germany Shanghai, China
Temperature Class Default	--
Terminator Box Location	D-End top
Two Speed Motor	No
Type of Duty	S1
UNSPSC	26101100
Voltage Code	D
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)

Categories

Motors and Generators → IEC Low Voltage AC Motors → General Performance Motors → IE3 Premium Efficiency Cast Iron Motors

