



RoadFlair Gen2

BRP493 LED285/NW 200W 220-240V DM GM

RoadFlair Gen2 - 28500 lm - 200 W - 4000 K

RoadFlair Gen2 is brand new design road lighting product family, set to meet customers' all-round requirements, including high lumen efficacy for energy saving and sustainability, aesthetic design for nice shape and appearance, quality material and components for product reliability and long lifetime, professional optics for various applications fulfillment, dimming and system control interface for improving municipal operations and offering future-proof features. RoadFlair Gen2 competitive price would help on the acceleration of road lighting LED transformation, to a more sustainable society and smarter city.

Product data

| | General Information |
|--------------------------------|--------------------------|
| 740 neutral white | Light source color |
| Yes | Driver included |
| Polycarbonate micro lens optic | Optical cover/lens type |
| Analog | Control interface |
| Screw connection block 3-pole | Connection |
| - | Cable |
| Safety class I | Protection class IEC |
| CE mark | CE mark |
| | |
| | Operating and Electrical |
| 220 to 240 V | Input Voltage |
| 50 or 60 Hz | Input Frequency |
| 0.95 | Power Factor (Min) |
| | |

| Yes | | |
|---|--|--|
| | | |
| | | |
| Aluminium pressure die cast | | |
| Polycarbonate | | |
| 519 mm | | |
| 297 mm | | |
| 136 mm | | |
| Aluminum and gray | | |
| | | |
| | | |
| IP66 [Dust penetration-protected, jet-proof] | | |
| IK08 [5 J vandal-protected] | | |
| | | |
| Initial Performance (IEC Compliant) | | |
| 28500 lm | | |
| | | |

Datasheet, 2021, October 20 data subject to change

RoadFlair Gen2


| Luminous flux tolerance | +/-10% |
|--------------------------------|----------|
| Initial LED luminaire efficacy | 140 lm/W |
| Init. Corr. Color Temperature | 4000 K |
| Init. Color Rendering Index | >70 |
| Initial input power | 200 W |
| Power consumption tolerance | +/-10% |
| | |

| Order product name | BRP493 LED285/NW 200W 220-240V DM GM |
|---------------------------------|--------------------------------------|
| Order code | 911401673506 |
| Numerator - Quantity Per Pack | 1 |
| Numerator - Packs per outer box | 1 |
| Material Nr. (12NC) | 911401673506 |
| Net Weight (Piece) | 6.600 kg |

| Power consumption toterance | 1/ =10 /6 |
|-----------------------------|---------------|
| | |
| Application Conditions | |
| Ambient temperature range | -40 to +50 °C |
| | |
| Product Data | |
| Full product code | 911401673506 |

IP 66 K 08

Dimensional drawing



BRP47x/BRP49x



© 2021 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. Philips and the Philips Shield Emblem are registered trademarks of Koninklijke Philips N.V.