



# RoadFlair Gen2

### BRP491 LED142/NW 100W 220-240V DM GM

RoadFlair Gen2 - 14200 lm - 100 W - 4000 K

RoadFlair Gen2 is brand new design road lighting product family, set to meet customers' all-round requirements, including high lumen efficacy for energy saving and sustainability, aesthetic design for nice shape and appearance, quality material and components for product reliability and long lifetime, professional optics for various applications fulfillment, dimming and system control interface for improving municipal operations and offering future-proof features. RoadFlair Gen2 competitive price would help on the acceleration of road lighting LED transformation, to a more sustainable society and smarter city.

#### **Product data**

General information	
Light source color	740 neutral white
Driver included	Yes
Optical cover/lens type	Polycarbonate micro lens optic
Control interface	Analog
Connection	Screw connection block 3-pole
Cable	-
Protection class IEC	Safety class I
CE mark	CE mark
Operating and electrical	
Input Voltage	220 to 240 V
Input Frequency	50 or 60 Hz
Power Factor (Min)	0.95

Controls and dimming		
Dimmable	Yes	
Mechanical and housing		
Housing Material	Aluminium pressure die cast	
Optical cover/lens material	Polycarbonate	
Overall length	355 mm	
Overall width	230 mm	
Overall height	136 mm	
Color	Aluminum and gray	
Approval and application		
Ingress protection code	IP66 [ Dust penetration-protected, jet-proof]	
Mech. impact protection code	IK08 [ 5 J vandal-protected]	
Initial performance (IEC compliant)		
Initial luminous flux (system flux)	14200 lm	

Datasheet, 2022, March 18 data subject to change

#### RoadFlair Gen2


Luminous flux tolerance	+/-10%
Initial LED luminaire efficacy	140 lm/W
Init. Corr. Color Temperature	4000 K
Init. Color Rendering Index	>70
Initial input power	100 W
Power consumption tolerance	+/-10%

Order product name	BRP491 LED142/NW 100W 220-240V DM GM
Order code	911401673306
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	1
Material Nr. (12NC)	911401673306
Net Weight (Piece)	3.600 kg

Application conditions	
Ambient temperature range	-40 to +50 °C
Product data	
Full product code	911401673306

## IP 66 K 08

#### Dimensional drawing



BRP491 LED142/NW 100W 220-240V DM GM



© 2022 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. Philips and the Philips Shield Emblem are registered trademarks of Koninklijke Philips N.V.