

PRODUCT-DETAILS

MP1-31R

MP1-31R Pushbutton



General Information

Extended Product Type	MP1-31R
Product ID	1SFA611100R3101
EAN	7320500261323
Catalog Description	MP1-31R Pushbutton
Long Description	Modular Pushbutton - Momentary - Flush - Red - Illuminated - Chrome metal - No contact block

Ordering

Minimum Order Quantity	10 piece
Customs Tariff Number	8536501999

Popular Downloads

Data Sheet, Technical Information	1SFC151007C02__
Instructions and Manuals	1SFC151011M0201

Dimensions

Product Net Width	0.029 m
Product Net Height	0.029 m

Product Net Depth / Length	0.033 m
Product Net Weight	0.024 kg

Technical

Ambient Air Temperature	Operation -25 ... +70 °C Storage -40 ... +85 °C
Color	Red
Actuator Type	Flush
Bezel Material	Chrome Metal
Illumination	Illuminated
Function	Momentary
Degree of Protection	Front IP66
Enclosure Type NEMA	Type1 Type12 Type13 Type3R Type4 Type4X
Mechanical Durability	2 million

Environmental

RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019
RoHS Date	0635 4
RoHS Information	2CMT2015-005452
WEEE Category	Product Not in WEEE Scope

Certificates and Declarations (Document Number)

cULus Certificate	9AKK107046A9925
Declaration of Conformity - CE	2CMT2015-005452
DNV GL Certificate	E-14107
Environmental Information	1SAC200079H0001
Instructions and Manuals	1SFC151011M0201
RoHS Information	2CMT2015-005452

Container Information

Package Level 1 Units	bag 1 piece
Package Level 1 Width	0.11 m
Package Level 1 Depth / Length	0.15 m
Package Level 1 Height	0.029 m
Package Level 1 Gross Weight	0.031 kg
Package Level 1 EAN	7320500261323

Classifications

Object Classification Code	S
ETIM 4	EC002024 - Accessories for control circuit devices
ETIM 5	EC000221 - Front element for push button

ETIM 6	EC000221 - Front element for push button
ETIM 7	EC000221 - Front element for push button
eClass	V11.0 : 27371210
UNSPSC	39121500
E-Number (Finland)	2313661
E-Number (Sweden)	3715301

Categories

Low Voltage Products and Systems → Control Products → Pilot Devices → Modular Plastic Range

