

PRODUCT-DETAILS

PSTX85-600-70

PSTX85-600-70 Softstarter



Información General

Global Commercial Alias	PSTX85-600-70
Extended Product Type	PSTX85-600-70
Product ID	1SFA898108R7000
ABB Type Designation	PSTX85-600-70
EAN	7320500501306
Catalog Description	PSTX85-600-70 Softstarter
Long Description	Softstarter PSTX85-600-70 for max 600V main voltage and 100 - 250V 50/60Hz control supply voltage.

Clasificación

Minimum Order Quantity	1 piece
Customs Tariff Number	85044090

Descargas Populares

Data Sheet, Technical Information	1SFC132009C0201
Instructions and Manuals	1SFC132081M0201

Dimensiones

Product Net Width	150.000 mm
Product Net Height	314.000 mm
Product Net Depth / Length	194.000 mm
Product Net Weight	6.10 kg

Technical

Rated Operational Voltage	208 ... 600 V AC
Rated Control Supply Voltage (U_s)	100 ... 250 V AC
Rated Control Circuit Voltage (U_c)	DC Operation 24 V
Rated Frequency (f)	Main Circuit 50/60 Hz
Rated Operational Power - In-Line Connection (P_e)	(230 V) 22 kW (400 V) 45 kW (500 V) 55 kW
Rated Operational Current - In-Line Connection (I_e)	85 A
Rated Operational Power - Inside Delta Connection	at 230 V 40 kW at 400 V 75 kW at 500 V 90 kW
Rated Operational Current - Inside Delta Connection	147 A
Service Factor Percentage	100 %
Overload Protection	Build-in electronic overload protection
Integrated Electronic Overload	Yes
Adjustable Rated Motor Current I_e	30 ... 100 %
Starting Capacity at Maximum Rated Current I_e	4xle for 10s
Ramp Time	1 ... 120 second [unit of time]
Initial Voltage During Start	10 ... 99 %
Step Down Voltage Special Ramp	100 ... 10 %
Current Limit Function	1.5 ... 7.5 xle
Switch for Inside Delta Connection	Yes
Run Signal Relay	Yes
By-pass Signal Relay	Yes
Fault Signal Relay	Yes
Overload Signal Relay	Yes
Analog Outputs	0...10 V, 0...20 mA, 4...20 mA
Signal indication ready to start/standby ON (LED)	Green
Signal indication running R (LED)	Green
Signal indication protection (LED)	Yellow

Signal indication fault (LED)	Red
Communication	Built in Modbus interface, Anybus, FieldBusPlug (with adapter).
Degree of Protection	acc. to IEC 60529, IEC 60947-1, EN 60529 Main Terminals IP00
Terminal Type	Cable Clamp
Connecting Capacity Main Circuit	Hole Diameter 8.5 mm
Connecting Capacity Control Circuit	Rigid 1x2.5 mm ²
Connecting Capacity Supply Circuit	Rigid 1x2.5 mm ²
Tightening Torque	Main Circuit 8 N·m
Product Main Type	PSTX85

Ambiente

Ambient Air Temperature	Almacenamiento -40 ... +70 °C Funcionamiento -25 ... +60 °C
RoHS Status	Following EU Directive 2002/95/EC August 18, 2005 and amendment

Certificados y Declaraciones (Número de Documento)

Declaration of Conformity - CE	2CMT005209
Environmental Information	2CMT005232
Instructions and Manuals	1SFC132081M0201
RoHS Information	2CMT005210

Información de Embalaje

Package Level 1 Width	230 mm
Package Level 1 Depth / Length	395 mm
Package Level 1 Height	280 mm
Package Level 1 Gross Weight	6.70 kg
Package Level 1 EAN	7320500501306
Package Level 1 Units	1 piece

Clasificaciones

Object Classification Code	Q
ETIM 4	EC002572 - Electronic motor control and protection device
ETIM 5	EC002572 - Electronic motor control and protection device
ETIM 6	EC002572 - Motor management device

Categorías

[Convertidores de frecuencia](#) → [Softstarters](#) → [Arranadores suaves](#) → [PSTX Softstarters](#) → [PSTX85](#)

