


SIRENA 120DB



Sirena di emergenza
Emergency siren
Sirène d'urgence

SCocca

SHELL
COQUILLE

PC

Colori Disponibili

AVAILABLE COLOURS
COULEURS DISPONIBLES



Servizio

OPERATION
FONCTIONNEMENT

 ∞

Tensione di Alimentazione

SUPPLY VOLTAGE
TENSION D'ALIMENTATION

12-24V AC/DC, 12-60V DC, 100 - 240V AC

Corrente Nominale

CURRENT CONSUMPTION
CONSOMMATION DE COURANT

	12	24	48	60	120	240
mA VDC	400	800	1300	1400		
mA VAC	600	110			280	150

Corrente Nominale Suoni EN54-3

SOUNDS RATED CURRENT EN54-3
SONS COURANT NOMINAL EN54-3

N°	Sound	F(Hz)	Times	24Vdc
7	Bi-Tone	554-440	0.1s/0.4s	700mA
20	Bi-Tone	490-610	0.25s/0.25s	700mA
32	Intermittent	490	0.5s ON/1s OFF	730mA
41	Linear	610	-	600mA
43	Linear	970	-	680mA
57	Sweep	1200-500	CYCLE 1s	700mA
59	Sweep	800-970	CYCLE 1s	720mA
67	Sweep	2450-2850	CYCLE 0.15s	650mA

Livello Sonoro

SOUND LEVEL
NIVEAU SONORE

Min 90dB
Max 120dB

Grado IK

IK RATING
DEGRE IK

IK08

Grado IP

IP RATING
DEGRE IP

IP66 - IP69k

Temperatura di Funzionamento

OPERATING TEMPERATURE
TEMPERATURE DE SERVICE

-40°C+60°C

Dati diffusi a solo scopo informativo. Sirena S.p.A. può modificare i dati in qualsiasi momento senza preavviso.
These data are disclosed only for information purposes. Sirena S.p.A. reserves the right to modify them at any time without prior notice.
Les données ne sont divulguées qu'à titre d'information. Sirena S.p.A. se réserve la faculté de les modifier à tout moment sans préavis

FUNZIONALITÀ

FUNCTIONALITY
FONCTIONNALITÉ

	SE120 STD	SE120 PRO
USB-C	NO	YES
MESSAGGI PERSONALIZZATI CONFIGURABILI DA PC PERSONALIZED MESSAGES CONFIGURABLE FROM PC MESSAGES PERSONNALISES CONFIGURABLES DEPUIS PC	NO	YES

CERTIFICAZIONI, OMOLOGAZIONI

CERTIFICATIONS, APPROVALS
CERTIFICATIONS, HOMOLOGATIONS

CE, UKCA

FISSAGGIO

MOUNTING
FIXATION

Tramite viti
By screws
Par vis

DISEGNO

TECHNICAL DRAWING
DESSIN
